

#	DATE	COMMENTS

© 2014 by Humphreys & Partners Architects, L.P.

Revised by: Humphreys & Partners Architects, L.P.

These drawings are for preliminary coordination only and not to be used for regulatory approval or construction.

STORRS CENTER PHASE 2 MANSFIELD, CT

EDR TRUST
MEMPHIS, TENNESSEE

HUMPHREYS & PARTNERS ARCHITECTS, L.P.

5339 ALPHA ROAD • SUITE 300 • DALLAS, TEXAS 75240
(972) 701-9636 • (972) 701-9639 FAX

DALLAS • ORLANDO • SAN RAMON
NEWPORT BEACH • SCOTTSDALE • NEW ORLEANS
www.humphreys.com



SHEET NO.
A4.37

SYMBOL LEGEND - EXTERIOR ELEVATION

	VENT CAP PER MEP		FINISH FLOOR ELEVATION TAG
	WALL SECTION TAG		TOP OF PLATE
	NON-COMBUSTIBLE FIRE WALL		TOP OF DECK SFC OF THE FIRE WALL
	AWNING TAG		TOP OF PARAPET
	ELEV. TAG		TOP OF FLOOR
	ELEV. TAG		TOP OF WINDOW
	ELEV. TAG		TOP OF DOOR
	ELEV. TAG		TOP OF PARAPET

ELEVATION NOTES

1. FINISH CONDITIONS SHALL MATCH THE FINISH CONDITIONS OF THE ADJACENT WALLS.
2. PROVIDE 1/2" MINIMUM OF SLOPE AWAY FROM WALL ON TOP SURFACE OF WALL PROJECTIONS.
3. PROVIDE EXTERIOR WALL LIGHT PROJECTIONS SO THAT THE BOTTOM OF THE EXTERIOR IS AT LEAST 4" FROM FACE OF WALL.
4. FLASHING AROUND ALL EXTERIOR STUD WALLS TO BE 1" THICK BELOW THE FINISH FLOOR.
5. FLASHING, WATERPROOF MEMBRANES, PROPER CALLS AND SEALANTS BACKER RODS AS REQUIRED) SHALL BE INSTALLED AROUND ALL WINDOWS, DOORS, ROOF TRANSOMS, TRUSS BALCONIES AND OTHER VERTICAL EXPOSED AREAS.
6. PROVIDE A WATER TIGHT BUILDINGS) ROOF AND EXTERIOR ENVELOPE THAT SHALL WATER PROOF AND BALCONIES TO BE SLOPED 1/8" PER 1' MINIMUM IN DIRECTION INDICATED ON PLANS AND AWAY FROM EXTERIOR WALLS.
7. PROVIDE 1/2" MINIMUM OF SLOPE AWAY FROM WALL ON TOP SURFACE OF WALL PROJECTIONS.
8. PER 2003 IRC SECTION 602.2.1(2) ARCHITECTURAL TRIM SHALL EXCEEDS 40% OF ARG TO THE WALL WITH METAL OR OTHER APPROVED NON-COMBUSTIBLE BRACKETS.



2 BUILDING TYPE VS 889 EAST ELEVATION
SCALE: 1/8" = 1'-0"



1 BUILDING TYPE VS 889 WEST ELEVATION
SCALE: 1/8" = 1'-0"